

LTC7138EMSE#PBF

Data Sheet

Conv DC-DC 4V to 140V Step Down Single-Out 0.8V to 140V 0.4A Automotive Medical 12-Pin MSOP EP Tube

Manufacturers	Analog Devices, Inc	and the second sec	
Package/Case	MSOP-16	555	\checkmark
Product Type	Power Management ICs	Time of the	Ó
RoHS			
Lifecycle		Images are for ref	erence only
Please submit RFQ f	or LTC7138EMSE#PBF or Email to us: sales@	ovaga.com We will contact you in 12 hours.	<u>RFQ</u>

General Description

The LTC7138 is a high efficiency step-down DC/DC regulator with internal power switch that draws only 12μ A typical DC supply current while maintaining a regulated output voltage at no load.

The LTC7138 can supply up to 400mA load current and features a programmable peak current limit that provides a simple method for optimizing efficiency and for reducing output ripple and component size. The LTC7138's combination of Burst Mode® operation, integrated power switch, low quiescent current, and programmable peak current limit provides high efficiency over a broad range of load currents.

With its wide input range of 4V to 140V and programmable overvoltage lockout, the LTC7138 is a robust regulator suited for regulating from a wide variety of power sources. Additionally, the LTC7138 includes a precise run threshold and soft-start feature to guarantee that the power system start-up is well-controlled in any environment. A feedback comparator output enables multiple LTC7138s to be connected in parallel for higher current applications.

The LTC7138 is available in a thermally enhanced high voltage-capable 16-lead MSE package with four missing pins.

Features

- Wide Operating Input Voltage Range: $4\mathrm{V}$ to $140\mathrm{V}$
- Internal Low Resistance Power MOSFET
- No Compensation Required
- Adjustable 100mA to 400mA Maximum Output Current
- Low Dropout Operation: 100% Duty Cycle
- Low Quiescent Current: $12\mu A$
- Wide Output Range: 0.8V to VIN
- $0.8V\pm1\%$ Feedback Voltage Reference
- Precise RUN Pin Threshold
- Internal or External Soft-Start
- Programmable 1.8V, 3.3V, 5V or Adjustable Output
- Few External Components Required
- Programmable Input Overvoltage Lockout
- Thermally Enhanced High Voltage MSOP Package

Related Products



LT3763EFE Analog Devices, Inc TSSOP28



LTC4417IUF Analog Devices, Inc QFN-24







LTM8045EY#PBF Analog Devices, Inc

BGA40





Application

Industrial Control Supplies

Medical Devices

Distributed Power Systems

Portable Instruments

Battery-Operated Devices

Avionics

Automotive

LT1038CK

Analog Devices, Inc TO-3

LTC3440EMS

Analog Devices, Inc MSOP10

LTC2990IMS#PBF

Analog Devices, Inc 10MSOP

LT4295IUFD#PBF

Analog Devices, Inc 28-WFQFN