

AD7718BRZ-REEL

Data Sheet

Analog to Digital Converters - ADC 24-Bit 8/10-Ch Lo Vtg Lo Pwr

Manufacturers <u>Analog Devices, Inc</u>

Package/Case SOIC-28

Product Type Data Conversion ICs

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for AD7718BRZ-REEL or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The AD7708/18 are complete analog front-ends for low frequency measurement applications. The AD7718 contains a 24-bit sigma delta ADC with PGA and can be configured as 4/5 fully-differential input channels or 8/10 pseudo-differential input channels. Two pins on the device are configurable as analog inputs or reference inputs. The AD7708 is a 16-bit version of the AD7718. Inputs signal ranges from 20mV to 2.56V can be directly converted using these ADCs. Signals can be converted directly from a transducer without the need for signal conditioning.

Features

8-/10-Channel, High Resolution Σ - Δ ADCs

24-Bit Resolution

Factory-Calibrated

Single Conversion Cycle Setting

Programmable Gain Front End

Simultaneous 50 Hz and 60 Hz Rejection

VREF Select TM Allows Absolute and Ratiometric Measurement Capability

Operation Can Be Optimized for- Analog Performance = 1)



Related Products



ADAS3022BCPZ
Analog Devices, Inc
LFCSP-40



AD7266BSUZ
Analog Devices, Inc
TQPF-32



AD574AJNZ
Analog Devices, Inc

PDIP-28



AD7938BSUZ

Analog Devices, Inc TQFP-32



AD7124-8BCPZ-RL7

Analog Devices, Inc LFCSP-32



AD7401YRWZ

Analog Devices, Inc SOIC-16



AD7192BRUZ-REEL

Analog Devices, Inc TSSOP-24



AD9680BCPZ-500

Analog Devices, Inc LFCSP-64