

## LTC2855IDE#TRPBF

Data Sheet

3.3V 20Mbps RS485/RS422 Transceiver with Integrated Switchable Termination; Package: DFN; No of Pins: 12; Temperature Range: -40°C to +85°C

Manufacturers <u>Analog Devices, Inc</u>

Package/Case QFN12

Product Type Interface ICs

RoHS Pb-free Halide free

Lifecycle



Images are for reference only

Please submit RFQ for LTC2855IDE#TRPBF or Email to us: sales@ovaga.com We will contact you in 12 hours.

**RFO** 

## **General Description**

The LTC2854 and LTC2855 are low power, 20Mbps RS485/RS422 transceivers operating on 3.3V supplies. The receiver includes a logic-selectable  $120\Omega$  termination, one-eighth unit load supporting up to 256 nodes per bus (C-, I-Grade), and a fail-safe feature that guarantees a high output state under conditions of floating or shorted inputs.

The driver maintains a high output impedance over the entire common mode range when disabled or when the supply is removed. Excessive power dissipation caused by bus contention or a fault is prevented by current limiting all outputs and by a thermal shutdown.

Enhanced ESD protection allows the LTC2854 to withstand  $\pm 25 \text{kV}$  (human body model) and the LTC2855 to withstand  $\pm 15 \text{kV}$  on the transceiver interface pins without latchup or damage.

Part NumberDuplexPackageLTC2854HalfDFN-10LTC2855FullSSOP-16, DFN-12

**Features** 

Integrated, Logic-Selectable  $120\Omega$  Termination Resistor

3.3V Supply Voltage

20Mbps Maximum Data Rate

No Damage or Latchup Up to  $\pm 25 kV HBM$ 

High Input Impedance Supports 256 Nodes (C-, I-Grade)

Operation Up to 125°C (H-Grade)

Guaranteed Fail-safe Receiver Operation Over the Entire Common Mode Range

Current Limited Drivers and Thermal Shutdown

Delayed Micropower Shutdown: 5µA Maximum (C-, I-Grade)

Power Up/Down Glitch-Free Driver Outputs

Low Operating Current: 370µA Typical in Receive Mode

Compatible with TIA/EIA-485-A Specifications

Available in 10-Pin 3mm × 3mm DFN, 12-Pin 4mm × 3mm DFN and 16-Pin SSOP Packages

## **Related Products**



LTC4300A-1IMS8#PBF

Analog Devices, Inc MSOP8



LTC2870IFE#PBF

Analog Devices, Inc TSSOP28




LTC6820HMS#PBF

Analog Devices, Inc MSOP-16



LTC2854HDD#PBF

Analog Devices, Inc OFN-10



Low Power RS485/RS422 Transceiver

Level Translator

Backplane Transceiver



LTC2870IUFD#PBF

Analog Devices, Inc 28-QFN



LTC6820IMS#PBF

Analog Devices, Inc MSOP16



**LTM2881IV-3#PBF** 

Analog Devices, Inc LGA32



LTC2852IDD#PBF

Analog Devices, Inc

DFN10