

8bit PIC Microcontroller, 64MHz, 16 kB Flash, 28-Pin SOIC

Manufacturers	<a href="#">Microchip Technology, Inc</a>
Package/Case	SOIC-28
Product Type	Embedded Processors & Controllers
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for PIC18F24K40-I/SO or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

## General Description

PIC18(L)F24K40 microcontrollers combine large Flash/EE/RAM memory, rich peripheral integration, XLP and 5V support to suit a variety of general purpose applications. These 28-pin devices deliver Core Independent Peripherals such as CWG, WWDT, CRC/Memory Scan, Hardware CVD, Zero-Cross Detect and Peripheral Pin Select, providing for increased design flexibility and lower system cost.

## Features

PIC18 Core with 83 Instructions, 31 Stack Levels

Internal 64MHz oscillator

Operating Voltage Range:- 'F' Version (2.3V – 5.5V)- Low Power 'LF' variant (1.8V – 3.6V)

Temperature Range:- Industrial Version (-40C to 85C)- Extended Version (-40C to 125C)

16 KB Flash Program Memory with self read/write capability

1024 Bytes Data SRAM Memory

256 Bytes of EEPROM

24 x 10-bit ADC channels

1 x 5-bit DAC

2 x Comparators

Fixed Voltage Reference (FVR) module - 1.024V, 2.048V and 4.096V output levels

Hardware Capacitive Voltage Divider (CVD) for miTouch buttons/sliders

1 x Zero-Cross Detect

1 x I2C/SPI

1 x EUSART with LIN support

CRC with Memory Scan

Windowed Watchdog Timer (WWDT)

1 x Hardware Limit Timer (HLT)

1 x Complementary Waveform Generator

2 x standalone 10-bit PWM modules

2 x Capture/Compare/PWM modules

Three 8-bit Timers/Counters

Four 16-bit Timers/Counters

1 x Hardware Limit Timer (HLT)

Extended Watchdog Timer (WDT)

eXtreme Low Power (XLP) technology

Doze, Idle, and Sleep Power Saving Operating Modes

Sleep mode: 50nA @ 1.8V, typical

Active mode: 32uA/MHz @ 1.8V, typical

Low Current Power-on Reset (POR)

Brown-out Reset (BOR)


Low-Power BOR (LPBOR)

Peripheral Pin Select

In-Circuit Debug Integrated On-Chip


In-Circuit Serial Programming (ICSP) via Two Pins

## **Related Products**



[PIC24F16KA101-I/SS](#)

Microchip Technology, Inc  
SSOP-20



[PIC16F1936-I/SS](#)

Microchip Technology, Inc  
SSOP-28




[PIC16F1938-I/SP](#)

Microchip Technology, Inc  
PDIP-28



[PIC18F23K22-I/SP](#)

Microchip Technology, Inc  
SPDIP-28



[PIC18F6520-I/PT](#)

Microchip Technology, Inc  
TQFP-64



[PIC18F2620-I/SP](#)

Microchip Technology, Inc  
SPDIP-28



[PIC18F2620-I/SO](#)

Microchip Technology, Inc  
SOIC-28



[PIC18F97J60T-I/PT](#)

Microchip Technology, Inc  
TQFP-100