

PIC32MZ2048EFH100-I/PT

Data Sheet

PIC/DSPIC Microcontroller, Floating Point Unit, PIC32 Family PIC32MZ EF Series Microcontrollers

Manufacturers	Microchip Technology, Inc	
Package/Case	TQFP-100	Junion and and
Product Type	Embedded Processors & Controllers	and a state of the
RoHS		
Lifecycle		Images are for reference only

Please submit RFQ for PIC32MZ2048EFH100-I/PT or Email to us: sales@ovaga.com We will contact you in 12 hours.

General Description

Features

252 MHz/415 DMIPS, MIPS Warrior M-class core
DSP-enhanced core:
Four 64-bit accumulators
Single-cycle MAC, saturating and fractional math
IEEE 754-compliant
Dual Panel Flash for live update support
FPU for fast single- and double-precision math
12-bit, 18 MSPS, 40-channel ADC module
Memory Management Unit for optimum embedded OS execution
microMIPS mode for up to 35% code compression
CAN, UART, I2C, PMP, EBI, SQI & Analog Comparators

SPI/I2S interfaces for audio processing and playback Hi-Speed USB 2.0 Device/Host/OTG 10/100 Mbps Ethernet MAC with MII and RMII interface Temperature Range: - 40°C to 85°C; - 40°C to 125°C AEC-Q100 Qualified Grade 1 Microcontroller Features Operating voltage range of 2.2V to 3.6V 2MB Flash memory (plus an additional 160 KB of Boot Flash) 512KB SRAM memory microMIPS mode for up to 35% smaller code size DSP-enhanced core: Four 64-bit accumulators Single-cylce MAC, saturating and fractional math IEEE 754-compliant FPU for fast single- and double-precision math Code-efficient (C and Assembly) architecture Low-power management modes (Idle and Sleep) Peripheral Features 50 MHz External Bus Interface (EBI) 50 MHz Serial Quad Interface (SQI) Peripheral Pin Select (PPS) functionality to enable function remap 8 channels of hardware programmable DMA and 18 channels of dedicated DMA with automatic data size detection Six UART modules (25 Mbps): Supports LIN 1.2 and IrDA protocols Two CAN modules 2.0B Active with DeviceNet addressing support Six 4-wire SPI modules (50 Mbps) SQI configurable as an additional SPI module (50 MHz) Five I2C modules (up to 1 Mbaud) with SMBus support

Ovaga Technologies Limited

Parallel Master Port (PMP)		
Hardware Real-Time Clock and Calendar (RTCC)		
Nine 16-bit Timers/Counters (four 16-bit pairs combine to create four 32-bit timers)		
Nine Capture inputs and Nine Compare/PWM outputs		
Audio/Graphics/Touch HMI Features		
Graphics interface: EBI or PMP		
Audio data communication: I2S, LJ, RJ, USB		
Audio data control interface: SPI and $I2C^{TM}$		
Audio data master clock: Fractional clock frequencies with USB synchronization		
Advanced Analog Features		
12-bit ADC Module:		
18 Msps rate with six Sample and Hold (S&H) circuits (five dedicated and one shared)		
Up to 40 analog inputs		
Can operate during sleep and idle modes		
Multiple trigger sources		
Six digital comparators and six digital filters		
Two analog comparators with 32 programmable voltage references		
Temperature sensor with ±2°C accuracy		
Debugger Development Support		
In-circuit and in-application programming		
4-wire MIPS® Enhanced JTAG interface		
Unlimited program and 12 complex data breakpoints		
IEEE 1149.2-compatible (JTAG) boundary scan		
Non-intrusive hardware-based instruction trace		
Integrated Software Libraries and Tools		
MPLAB Harmony - PIC32 software development framework		
C/C++ compiler with native DSP/fractional and FPU support		
TCP/IP, USB, Graphics and mTouch middleware		

Ovaga Technologies Limited

MFi, Android and Bluetooth audio frameworks

RTOS Kernels, Express Logic ThreadX, FreeRTOS, OPENRTOS, Micriµm, µC/OS and SEGGER embOS

Related Products



PIC24F16KA101-I/SS

Microchip Technology, Inc SSOP-20

PIC16F1938-I/SP

Microchip Technology, Inc PDIP-28



ovag

<u>PIC18F6520-I/PT</u>

Microchip Technology, Inc TQFP-64

PIC18F2620-I/SO

Microchip Technology, Inc SOIC-28









PIC16F1936-I/SS

Microchip Technology, Inc SSOP-28

PIC18F23K22-I/SP

Microchip Technology, Inc SPDIP-28

PIC18F2620-I/SP

Microchip Technology, Inc SPDIP-28

PIC18F97J60T-I/PT

Microchip Technology, Inc TQFP-100