



Data Sheet

Operational Amplifier, RRIO, 2 Amplifier, 10 MHz, 7 V/µs, 2.5V to 5.5V, TSSOP, 8 Pins

Manufacturers <u>Microchip Technology</u>, Inc

Package/Case TSSOP-8

Product Type Amplifier ICs

**RoHS** 

Lifecycle



Images are for reference only

Please submit RFQ for MCP6022-I/ST or Email to us; sales@ovaga.com We will contact you in 12 hours.

**RFO** 

## **General Description**

The MCP6022 dual operational amplifier (op amp) has a gain bandwidth product of 10 MHz with a low typical operating current of 1.0 mA and an offset voltage that is less than 0.5 mV. The MCP6022 uses Microchip's advanced CMOS technology, which provides low bias current, high-speed operation, high open-loop gain, and rail-to-rail output swing. The MCP6022 operates with a single supply voltage that can be as low as 2.5V, while drawing less than 1.35 mA of quiescent current per amplifier. The MCP6022 is available in standard 8-lead PDIP, SOIC and TSSOP packages. This amplifier is ideal for battery and loop-powered applications as well as industrial process control, low-power battery-operated devices, portable equipment, data acquisition equipment, test equipment and low-end audio applications. AEC-Q100 Grade 1 qualification is available for this device

## **Features**

Trimmed for Low Offset Voltage

10MHz Gain Bandwidth Product

Rail-to-Rail Input/Output

Unity Gain Stable

Specified over the Extended Temperature Range

Small 8-pin TSSOP Package

AEC-Q100 Grade 1 qualification

## **Related Products**



MCP6S28-I/SL

Microchip Technology, Inc SOIC-16



MCP6V11T-E/OT

Microchip Technology, Inc SOT-23-5



MCP6024-I/SL

Microchip Technology, Inc SOIC-14



MCP604-E/SL

Microchip Technology, Inc SOIC-14



MCP6V31T-E/OT

Microchip Technology, Inc SOT-23-5



MCP6L01T-E/OT

Microchip Technology, Inc SOT-23-5



MCP6022-I/SN

Microchip Technology, Inc SOIC-8



MCP602T-I/SN

Microchip Technology, Inc SOIC-8