



Data Sheet

Dual / Quad SPST, CMOS Analog Switches

Manufacturers Renesas Technology Corp

Package/Case CDIP-16

Product Type Interface ICs

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for HI1-0201-2 or Email to us; sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The HI-201/883 is a monolithic device comprised of four independently selectable SPST switchers which feature fast switching speeds (185ns typical) combined with low power dissipation (15mW typical at +25°C). Each switch provides low ON resistance operation for input signal voltages up to the supply rails and for signal currents up to 25mA continuous. Rugged DI construction eliminates latchup and substrate SCR failure modes. All devices provide break-before-make switching and are TTL and CMOS compatible for maximum application versatility. The HI-201/883 is an ideal component for use in high frequency analog switching. Typical applications include signal path switching, sample and hold circuits, digital filters, and op amp gain switching networks. HI-201/883 is available in a 16 Ld CerDIP package.

Features

Pb-Free Available (RoHS Compliant)

Analog Voltage Range ±15V


Analog Current Range 80mA

Turn-On Time 240ns

Low r_{ON} 55 Ω

Low Power Dissipation 15mW

TTL/CMOS Compatible



Related Products



HIN202EIBNZ
Renesas Technology Corp
SOIC-16



Renesas Technology Corp CDIP-16

HI1-0508-2



HI1-5051-2
Renesas Technology Corp
CDIP-16



HIN213EIAZ-T
Renesas Technology Corp
SSOP-28



HII-0546-2 Renesas Technology Corp CDIP-28



HII-5042-2 Renesas Technology Corp CDIP-16



HIN213ECAZ-T

Renesas Technology Corp

SSOP-28



HI3-0547-5Z

Renesas Technology Corp

CDIP-28