

MCP41010-E/SN

Data Sheet

Digital Pot, 256 steps, SPI, 10kohms, single channel, -40C to +125C, 8-SOIC 150mil, TUBE, Digital Potentiometer ICs 256 Step SPI 10kOhm

Manufacturers <u>Microchip Technology, Inc</u>

Package/Case SOIC-8

Product Type Digital Potentiometer ICs

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for MCP41010-E/SN or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The MCP41010 is a single-channel, 8-bit digital potentiometer features $10k\Omega$ end-to-end resistance value with an SPI serial interface. The wiper position varies linearly and is controlled via the SPI interface. The MCP41010 has outstanding AC and DC characteristics, and consumes $<1~\mu$ A during static operation. Applications for the MCP41010 digital potentiometer include audio equipment (volume and tone controls), servo-motor control, battery charging and control, communications (line impedance matching), power supplies, instrumentation (gain, offset adjust), LCD contrast control and programmable filters. The MCP41010 is available in 8-pin PDIP and SOIC packages.

Features

Single Resistor Network

Potentiometer or Rheostat configuration options

Resistor Network Resolution

8-bit: 255 Resistors (256 Steps)

RAB Resistances options of:

 $10k\Omega$

Zero-Scale to Full-Scale Wiper operation

INL: 1LSB (max)

DNL: 1LSB (max)

SPI Compatible Serial interface

Standby current: 1uA (max)

Wide Operating Voltage: 2.7V to 5.5V

Wide Bandwidth (-3dB) Operation: 1 MHz (typ.)

Extended temperature range: -40°C to +125°C

Related Products



MCP4352T-104E/ST

Microchip Technology, Inc TSSOP-14





Microchip Technology, Inc TSSOP-14



Microchip Technology, Inc TSSOP-14

MCP41HV51-104E/ST



MCP4661T-103E/ML

Microchip Technology, Inc QFN-16

MCP45HV51-502E/ST



Microchip Technology, Inc TSSOP-14

MCP41HV51-103E/ST



Microchip Technology, Inc TSSOP-14

MCP42100-I/SL



Microchip Technology, Inc SOIC-14



MCP4461-103E/ST

Microchip Technology, Inc TSSOP-20