



Data Sheet

+3.3 V/+5 V, Low Power, Quad 12-Bit CMOS DAC; Package: SOIC - Wide; No of Pins: 28; Temperature Range: Commercial

Manufacturers <u>Analog Devices, Inc</u>

Package/Case SOIC-28

Product Type Data Conversion ICs

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for AD7564BRZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFQ

General Description

The AD7564 contains four 12-bit DACs in one monolithic device. The DACs are standard current output with separate VREF, IOUT1, IOUT2 and RFB terminals. These DACs operate from a single +3.3 V to +5 V supply.

The AD7564 is a serial input device. Data is loaded using FSIN, CLKIN and SDIN. Two address pins A0 and A1 set up a device address, and this feature may be used to simplify device loading in a multi-DAC environment. Alternatively, A0 and A1 can be ignored and the serial out capability used to configure a daisy-chained system. All DACs can be simultaneously updated using the asynchronous LDAC input, and they can be cleared by asserting the asynchronous CLR input.

The device is packaged in 28-pin SOIC, SSOP and DIP packages.

Features

Four 12-Bit DACs in One Package

4-Quadrant Multiplication

Separate References

Single Supply Operation

Guaranteed Specifications with +3.3V/+5 Supply

Low Power

Versatile Serial Interface

Simultaneous Update Capability

Reset Function


28-Pin SOIC, SSOP and DIP Packages

Application

Process control

Portable instrumentation

General purpose test equipment





Related Products



ADAS3022BCPZ
Analog Devices, Inc
LFCSP-40



AD574AJNZ
Analog Devices, Inc
PDIP-28



AD7938BSUZ
Analog Devices, Inc
TQFP-32



AD7266BSUZ

Analog Devices, Inc
TQPF-32



AD7401YRWZ

Analog Devices, Inc

SOIC-16



AD7192BRUZ-REEL
Analog Devices, Inc
TSSOP-24



AD7124-8BCPZ-RL7
Analog Devices, Inc
LFCSP-32



Analog Devices, Inc LFCSP-64